

cast film lines

SML
EXTRUSION LINES – ENGINEERED TO PERFORM ▶

▶ STRETCH WRAP FILM

SmartCast®



**Extrusion lines –
engineered to perform**

Modular, flexible, powerful


The SmartCast[®] line stands for a high performance and variety since it offers an outstanding number of equipment features.

The SmartCast[®] is remarkable for its modular system consisting of four pre-configured extrusion units. This unique characteristic allows outputs ranging from 1,900 to 3,000 kg/h.


► Key Features

- Compact design and low space requirements
- Low power consumption thanks to energy-saving extrusion technology
- High production flexibility owing to quick changeover times
- Excellent production stability at high speeds

SmartCast[®] 5L




SmartCast[®] 7L



Products:

- Super power stretch
- Automatic stretch
- Hand stretch
- Cling film





PRODUCT SPECIFICATIONS

Products	super power stretch, automatic stretch, hand stretch, cling film	
Film thickness range	8 - 50 µm	
Film final width	6 x 500 mm	
Film structure	5 or 7 layers	
Production speed	up to 800 m/min	
Net output value SmartCast[®] XL	12 µm	1,400 kg/h
	17 µm	2,000 kg/h
	23 µm	2,400 kg/h

EXTRUDER CONFIGURATIONS

SmartCast[®] S 5L	SmartCast[®] M 7L	SmartCast[®] L 5L	SmartCast[®] XL 7L
Gravimetric batch dosing system with 2 components. Option: 3 or 4 components			
5 extruders	6 extruders	5 extruders	6 extruders
2 x 90/33 each 600 kg/h	2 x 90/33 each 750 kg/h	2 x HSE 90/33 each 950 kg/h	2 x HSE 90/33 each 950 kg/h
1 x 75/33 480 kg/h	4 x 60/28 each 240 kg/h	1 x 90/33 600 kg/h	4 x 75/33 each 300 kg/h
2 x 60/28 240 kg/h		2 x 75/33 each 300 kg/h	
SML advanced heaters for the extruder barrels			
Edge encapsulation extruder 45/28D (optional)			Edge encapsulation
5-layer feedblock	7-layer feedblock	5-layer feedblock	7-layer feedblock
Automatic flat die: 3,800 mm			

WINDING UNIT
Winder W4000-4S



CHILL ROLL UNIT

- ▶ Primary chill roll Ø 1,200 mm or 1,600 mm, width 3,800 mm
- ▶ Optional secondary chill roll Ø 400 mm, width 3,800 mm
- ▶ Automatic positioning
- ▶ IR thickness measurement
- ▶ Alternative: X-ray or Beta sensor
- ▶ Oscillating frame
- ▶ Cut-resistant guiding rolls

WINDER W4000-4S

- ▶ Machine and jumbo rolls (up to 60 kg) on 3-inch cores
- ▶ Hand rolls on 2-inch cores
- ▶ Thin core technology
- ▶ Shortest cycle time
- ▶ Ultimate short film tail for a perfect roll finish
- ▶ Optional: coreless winding

Alternative: Winder W4000-2S and winder W3000-4S are available for **SmartCast[®]** lines.

EDGE TRIM REFEEDING SYSTEM

- ▶ Recycling unit with reel feeder for the pelletising of edge trims and start-up rolls.
Alternative: Vertical scraptruder (fluff refeeding system).

Superior film and winding quality
Ultra short film tail for a perfect roll finish
Thin core technology

▶ **Take advantage
of our global
leadership in
extrusion
technology.**

**ANALYSES
DEVELOPMENT
PRE-TESTED PERFORMANCE
DELIVERY ON TIME
SERVICE SUPPORT
CUSTOMER SATISFACTION**

SML
EXTRUSION LINES – ENGINEERED TO PERFORM ▶

SML - Head Office

Gewerbepark Ost 32
4846 Redlham
Austria
Phone: +43 7673 90999
E-mail: sml@sml.at
www.sml.at

SML - Machinery Far East Sdn Bhd

(1029958-P)
1201 Block B, Menara Amcorp
No.18 Jalan Persiaran Barat
46050 Petaling Jaya
Selangor Darul Ehsan,
Selangor, Malaysia
Phone: +60 3 7955 9098
E-mail: yen@sml.at

SML - Moscow Office

Ogorodny proezd, 5
Building 3, office 408
127254 Moscow
Russia
Phone: +7 495 618 8007
E-mail: kna@sml.at

SML - Beijing Office

Unit 1410, Landmark Tower
No. 8 North Dongsanhuan Road
Chaoyang District
100004 Beijing, P.R. of China
Phone: +86 10 6590 0946
E-mail: sml@sml.bj.cn

SML - North America Service, Inc.

Suite 204
85 Eastern Avenue
Gloucester MA 01930
USA
Phone: +1 978 281 0560
Mobile: +1 978 394 1553
E-mail: jom@sml.at



www.sml.at